Material Safety Data Sheet

24-Hour Emergency Telephone Number 1-800-424-9300 (Chemtree)



MSDS #: 10006

HMIS Ratings:

HEALTH:

FLAMMABILITY: 0

REACTIVITY: 0

PROTECTION:

MSDS #: 10006 DATE OF PREPARATION: 1/7/03

LAST REVISION DATE: 1/7/03

SECTION OF TROPUCE IDENTIFICATION OF THE SECTION OF

PRODUCT NAME:

SWEDISH FORMULA HARD SURFACE CLEANER

PRODUCT DESCRIPTION: WATERBASED FLOOR CLEANER

SECTION UTHAY ARD QUSINGREDIENTS IN THE SECTION OF THE SECTION OF

Occupational

Exposure Limits

VAPOR PRESSURE-

INGREDIENT

% WEIGHT ACGIH-TLV OSHA-PEL min Hg CAS#

NONE

THE PROPERTY OF THE PROPERTY O

BOILING RANGE:

>212F (100C)

EVAPORATION RATE: Slower than n-Butyl Acetate

% VOLATILE - WT: 98

DENSITY:

8.30 LBS/GAL (1.00KG/L)

VAPOR DENSITY:

Heavier than air

SOLUBILITY IN WATER: Miscible

PRODUCT CHARACTERISTICS: Aquamarine, water-thin liquid with fresh odor

SECTIONAL SERVICE DESCRIPTION OF THE SECTION OF THE

FLAMMABILITY CLASSIFICATION: Non-Flammable

FLASH POINT: Over 200F (93C) PMCC

% OF VOL. OF FLAMMABLE LIMITS (Upper): N/A

(Lower): N/A

EXTINGUISHING MEDIA: Foam, Carbon Dioxide, Dry Chemical

UNUSUAL FIRE

EXPLOSION

Closed containers may explode (due to the build-up of steam pressure) when exposed to extreme heat.

HAZARDS:

SPECIAL

FIREFIGHTING PROCEDURES:

Water may be used to cool closed containers to prevent pressure build-up.

Material Safety Data Sheet

24-Hour Emergency Telephone Number 1-800-424-9300 (Chemtree)



MSDS #: 10006

HYGIENIC PRACTICES:

Wash hands with soap and water before eating or using rest rooms.

THE TRANSCEPTION OF THE PROPERTY OF THE PROPER

Do not transfer contents to bottles or other unlabeled containers. Do not store in high temperature (above 100F or 38C) environment. Keep from freezing.

KEEP OUT OF THE REACH OF CHILDREN

KEY CODE

HMIS = Hazardous Materials Information System

- 0 = Minimal Hazard
- 1 = Slight Hazard
- 2 = Moderate Hazard
- 3 = Serious Hazard
- 4 = Severe Hazard
- N/A = Not Applicable
- N/E = Not Established
- ACGIH = American Conference of Governmental Industrial Hygienists
- OEL Occupational Exposure Limits
- PEL = Permissible Exposure Limit = exposure limit to an airborne contaminant in a workday set by OSHA
- TLV = Threshold Limit Value = Time-weighted average concentration for a normal 8-hour workday without adverse effect.
- IARC = International Agency for Research on Cancer
- NTP = National Toxicology Program
- OSHA = Occupational Safety and Health Administration

For additional health and safety information, call the BonaKemi Compliance Department at (303) 371-1411.

The identities of ingredients are withheld as proprietary information. The information on this data sheet represents our best opinion as to the proper use and handling of this product under normal conditions, based upon information compiled from sources considered to be dependable. It is accurate and reliable to the best of our knowledge and belief, but is not guaranteed to be so. It is the user's responsibility to determine the suitability of this product for a specific purpose and to adopt such safety precautions as may be necessary. Any use of the product which is not in conformance with this data sheet or which involves using the product in combination with any other product or any other process is the responsibility of the user.

BEFORE USING ANY PRODUCT, READ THE LABEL.